

ENCORE CAPE & TWO STORY PLANS

STANDARD COMPARISON SHEET

INTERIOR

	Ours	Theirs
1. 8 Foot ceiling height	<input checked="" type="checkbox"/>	<input type="checkbox"/>
2. Smooth 1/2" drywall throughout all rooms (including closets)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
3. Smooth 5/8" drywall ceilings throughout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
4. Painted drywall walls and ceiling (one coat primer)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
5. Drywall ceiling corners to sidewall	<input checked="" type="checkbox"/>	<input type="checkbox"/>
6. White wood colonial 2 1/4" case molding at windows and doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
7. White wood colonial 3 1/4" base molding throughout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
8. White wood window and door jambs	<input checked="" type="checkbox"/>	<input type="checkbox"/>
9. White wood window sills	<input checked="" type="checkbox"/>	<input type="checkbox"/>
10. White 6-panel doors with 3 mortised hinges	<input checked="" type="checkbox"/>	<input type="checkbox"/>
11. 30" interior passage doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
12. Privacy locks on bath doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
13. Door stop bumpers all doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
14. 25 oz. FHA grade carpet throughout (excluding wet areas)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
15. Dupont stain protected carpet	<input checked="" type="checkbox"/>	<input type="checkbox"/>
16. 5.5 lb. Rebond carpet pad	<input checked="" type="checkbox"/>	<input type="checkbox"/>
17. Tack strip carpet installation	<input checked="" type="checkbox"/>	<input type="checkbox"/>
18. Vinyl floor at foyer entry	<input checked="" type="checkbox"/>	<input type="checkbox"/>
19. Vinyl floor coverings in kitchen, morning rooms, baths and utility	<input checked="" type="checkbox"/>	<input type="checkbox"/>
20. Wire shelves in all closets (pantries and linens have 3)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
21. Brass base and globe interior lights (B-1) (excluding bedrooms)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
22. Glass and brass light (B-9) standard in morning room	<input checked="" type="checkbox"/>	<input type="checkbox"/>

KITCHEN

23. KCMA approved residential panel oak cabinet doors and drawers with oak styles	<input checked="" type="checkbox"/>	<input type="checkbox"/>
24. 1/2 Depth shelves in base cabinets for extra storage	<input checked="" type="checkbox"/>	<input type="checkbox"/>
25. Adjustable overhead cabinet shelves	<input checked="" type="checkbox"/>	<input type="checkbox"/>
26. Dual roller guide system with solid oak drawer fronts over base doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
27. Concealed hinges on cabinet doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
28. Cabinet pulls	<input checked="" type="checkbox"/>	<input type="checkbox"/>
29. Broan ventless range hood	<input checked="" type="checkbox"/>	<input type="checkbox"/>
30. Laminate countertops w/self edge and 4" backsplash	<input checked="" type="checkbox"/>	<input type="checkbox"/>
31. 7" Deep double bowl stainless steel sink	<input checked="" type="checkbox"/>	<input type="checkbox"/>
32. Moen single lever faucet w/spray	<input checked="" type="checkbox"/>	<input type="checkbox"/>
33. 36" wide refrigerator openings	<input checked="" type="checkbox"/>	<input type="checkbox"/>
34. Wired for electric range	<input checked="" type="checkbox"/>	<input type="checkbox"/>
35. GFI wired kitchen receptacles	<input checked="" type="checkbox"/>	<input type="checkbox"/>
36. Brass base (B-1) drum light over kitchen sink and in center of kitchen	<input checked="" type="checkbox"/>	<input type="checkbox"/>

BATHS

37. Fiberglass tubs and showers all baths	<input checked="" type="checkbox"/>	<input type="checkbox"/>
38. 60" Fiberglass tub/shower Main Bath	<input checked="" type="checkbox"/>	<input type="checkbox"/>
39. 60" Fiberglass tub/shower Master Bath (some models)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
40. Fiberglass garden tub with walls (some models)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
41. Fiberglass corner tub with separate shower stall (some models)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
42. Moen single lever faucet at lavs	<input checked="" type="checkbox"/>	<input type="checkbox"/>
43. Moen single lever anti-scald faucet on showers	<input checked="" type="checkbox"/>	<input type="checkbox"/>
44. Porcelain vanity bowls in all baths	<input checked="" type="checkbox"/>	<input type="checkbox"/>
45. Pop up drain assemblies in all vanity bowls and tubs	<input checked="" type="checkbox"/>	<input type="checkbox"/>
46. GFI wired bath receptacles	<input checked="" type="checkbox"/>	<input type="checkbox"/>
47. Power vent ceiling fans with lights	<input checked="" type="checkbox"/>	<input type="checkbox"/>
48. Beveled mirror over all vanity bowls	<input checked="" type="checkbox"/>	<input type="checkbox"/>
49. Chrome sconce light over all vanity bowls (W-3)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
50. 1.6 Gallon porcelain toilets w/elongated bowl	<input checked="" type="checkbox"/>	<input type="checkbox"/>
51. Panel oak cabinets in all baths	<input checked="" type="checkbox"/>	<input type="checkbox"/>

UTILITIES

52. HVAC Boots, Registers and cold air returns (2 stories have registers and cold air returns on 1st floor only)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
53. 42 Gallon electric energy saving water heater	<input checked="" type="checkbox"/>	<input type="checkbox"/>
54. Full size 200 amp main service with circuit breaker protection	<input checked="" type="checkbox"/>	<input type="checkbox"/>

Ours Theirs

55. GFI protection for two exterior receptacles (one front and one rear)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
56. PVC drain lines	<input checked="" type="checkbox"/>	<input type="checkbox"/>
57. Copper water lines stubbed through the floor	<input checked="" type="checkbox"/>	<input type="checkbox"/>
58. AC/DC Smoke detectors in all bedrooms (ship loose for basement)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
59. Water shut off valves throughout	<input checked="" type="checkbox"/>	<input type="checkbox"/>
60. Bi-fold doors in washer dryer area (some plans)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
61. Switched receptacle each bedroom	<input checked="" type="checkbox"/>	<input type="checkbox"/>
62. Vented wire shelf in all utility areas	<input checked="" type="checkbox"/>	<input type="checkbox"/>
63. Washer plumbing	<input checked="" type="checkbox"/>	<input type="checkbox"/>
64. Wire for dryer (110 or 220)	<input checked="" type="checkbox"/>	<input type="checkbox"/>

EXTERIOR AND CONSTRUCTION

65. Joist hangers on mating wall floor joists with solid block bridging	<input checked="" type="checkbox"/>	<input type="checkbox"/>
66. 1st Floor - 2 10 Floor joists @ 16" O.C. with double perimeter sidewall	<input checked="" type="checkbox"/>	<input type="checkbox"/>
67. Two story 2nd Floor - 2 10 Floor joists @ 16" O.C. w/double perimeter sidewall (non-plumbing modules)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
68. Open Joist 2000 used in two story second floor bath modules @ 19.2" O.C.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
69. 2 6 Exterior walls @ 24" O.C. (16" O.C. optional)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
70. 7/16" OSB sheathing on sidewalls and endwalls	<input checked="" type="checkbox"/>	<input type="checkbox"/>
71. Sub floor 3/4" (nominal) OSB floor decking	<input checked="" type="checkbox"/>	<input type="checkbox"/>
72. 2 4 interior partitions @ 24" O.C.	<input checked="" type="checkbox"/>	<input type="checkbox"/>
73. Double marriage walls 8" (2 4 @ 16" O.C.)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
74. 5/12 Pitch roof trusses @ 24" O.C. with integral knee wall on Two Story	<input checked="" type="checkbox"/>	<input type="checkbox"/>
75. 12/12 Pitch roof trusses @ 24" O.C. on Cape	<input checked="" type="checkbox"/>	<input type="checkbox"/>
76. 1/2" OSB roof sheathing with H-clips	<input checked="" type="checkbox"/>	<input type="checkbox"/>
77. Ply Dry shingle underlayment	<input checked="" type="checkbox"/>	<input type="checkbox"/>
78. 25 Year self sealing fiberglass shingles	<input checked="" type="checkbox"/>	<input type="checkbox"/>
79. Shingle over ridge vent (shipped loose)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
80. 9" Vented overhangs on front & rear w/vinyl soffit - Two Story	<input checked="" type="checkbox"/>	<input type="checkbox"/>
81. 10" Vented overhangs on gable ends w/vinyl soffit - Two Story	<input checked="" type="checkbox"/>	<input type="checkbox"/>
82. 6" Vented overhangs and gable ends on Cape Cod models	<input checked="" type="checkbox"/>	<input type="checkbox"/>
83. 6" Aluminum fascia over 2 6 for easier gutter mounting	<input checked="" type="checkbox"/>	<input type="checkbox"/>
84. Vinyl thermopane windows with screens and bottom tilt	<input checked="" type="checkbox"/>	<input type="checkbox"/>
85. Window grids and Low-E glass	<input checked="" type="checkbox"/>	<input type="checkbox"/>
86. 6-Panel 3/0 6/8 insulated steel front door w/peep	<input checked="" type="checkbox"/>	<input type="checkbox"/>
87. 6-Panel 2/8 6/8 insulated steel rear door	<input checked="" type="checkbox"/>	<input type="checkbox"/>
88. White torch light front and rear door (B-6)	<input checked="" type="checkbox"/>	<input type="checkbox"/>
89. 5 5 or 4 4 Vinyl siding with 2 piece F-channel and cove	<input checked="" type="checkbox"/>	<input type="checkbox"/>
90. 2 6 Headers over windows and doors	<input checked="" type="checkbox"/>	<input type="checkbox"/>
91. Floor mating beam of 1st floor comprised of (4) LVL (2 per module)	<input checked="" type="checkbox"/>	<input type="checkbox"/>

INSULATION

92. R-30 blown-in insulation w/vapor barrier in ceiling	<input checked="" type="checkbox"/>	<input type="checkbox"/>
93. R-19 fiberglass batt insulation (6") w/vapor barrier in sidewalls	<input checked="" type="checkbox"/>	<input type="checkbox"/>
94. Basement entry walls standard with R-7 insulation	<input checked="" type="checkbox"/>	<input type="checkbox"/>
95. Foam gaskets on all exterior wall receptacles and switches	<input checked="" type="checkbox"/>	<input type="checkbox"/>
96. Foam sealed around windows to stop air infiltration	<input checked="" type="checkbox"/>	<input type="checkbox"/>

MISCELLANEOUS

97. Panel bo is dropped to basement	<input checked="" type="checkbox"/>	<input type="checkbox"/>
-------------------------------------	-------------------------------------	--------------------------

At Ritz-Craft we are constantly searching for new and better ways to build homes. We therefore reserve the right to change product specifications, plans and prices without notice and without incurring obligations.

Artist's rendering(s) shown may contain optional or suggested features.